

Máquina Asic Miner Hashrate 20.5TH/s BTC Antminer

| Detailed Characteristics | | Value | | |
|---|-----------------------|-------|----------|-----------|
| | | Min | Typ | Max |
| Hashrate & Power | | | | |
| Hashrate, TH/s | Normal | | 20.50 | 20.95 |
| | Low Power | | 16~17.50 | +3% (1-1) |
| Power efficiency on wall @25°C, J/TH | Normal | 70.00 | | 74.90 |
| | Low Power | 64.00 | | 68.48 |
| Power efficiency on wall @40°C, J/TH | Normal | 74.54 | | 79.75 |
| | Low Power | 67.45 | | 72.18 |
| Power on wall, Watt (1-2) | Normal | 1435 | | 1671 |
| | Low Power | 1024 | | 1301 |
| Power supply AC input voltage, Volt (1-3) | | 200 | 220 | 240 |
| Power supply AC input current, Amp(1-4) | Normal | | 6.52 | 8.36 |
| | Low Power | | 4.65 | 6.32 |
| Power supply Input AC Frequency Range, Hz | | 47 | 50 | 63 |
| Hardware Configuration | | | | |
| Quantity of hash chips | 252 | | | |
| Quantity of hash boards | 3 | | | |
| Networking connection mode | RJ45 ethernet 10/100M | | | |
| Miner Size(Length*Width*Height, w/o | 238*175.4*278.8 | | | |
| Net weight, kg (2-2) | 7.6 | | | |
| Noise, dBA @25°C (2-3) | | | | 76 |









