

# Bitmain antminer S17 Pro 53T Hash Rate con fuente de alimentación Bitcoin Miner

<b>Hashrate &amp; Power</b>				
Hashrate, <b>TH/s</b>	Low Power		<b>36~48.00</b>	<b>+3% (1-1)</b>
	Normal		<b>53</b>	<b>55.95</b>
	Turbo		<b>53~62.00</b>	<b>+3% (1-2)</b>
Power efficiency on wall @ <b>25°C</b> , <b>J/TH</b>	Low Power	<b>36.00</b>		<b>39.60</b>
	Normal	<b>39.50</b>		<b>43.45</b>
	Turbo	<b>45.00</b>		<b>49.50</b>
Power efficiency on wall @ <b>40°C</b> , <b>J/TH</b>	Low Power	<b>38.22</b>		<b>42.05</b>
	Normal	<b>41.73</b>		<b>45.90</b>
	Turbo	<b>47.99</b>		<b>52.79</b>
Power on wall, <b>Watt (1-3)</b>	Low Power	<b>1296~1728</b>		<b>2079</b>
	Normal	<b>2094</b>		<b>2568</b>
	Turbo	<b>2385~2790</b>		<b>3371</b>
Power supply AC input voltage, <b>Volt (1-4)</b>		<b>200</b>	<b>220</b>	<b>240</b>
Power supply AC input current, <b>Amp(1-5)</b>	Low Power		<b>5.89~7.85</b>	<b>10.40</b>
	Normal		<b>9.52</b>	<b>12.84</b>
	Turbo		<b>10.84~12.68</b>	<b>16.86</b>
Power supply Input AC Frequency Range, <b>Hz</b>		<b>47</b>	<b>50</b>	<b>63</b>
<b>Hardware Configuration</b>				
Quantity of hash chips	<b>144</b>			
Quantity of hash boards	<b>3</b>			
Networking connection mode	<b>RJ45 Ethernet 10/100M</b>			
Miner Size (Length*Width*Height, w/o package),mm(2-1)	<b>298.2*178.0*296.6</b>			
Net weight, <b>kg (2-2)</b>	<b>9.5</b>			
Noise, <b>dba @25°C (2-3)</b>				<b>82</b>
<b>Environment Requirements</b>				
Operation temperature,°C		<b>0</b>	<b>25</b>	<b>40</b>
Storage temperature,°C		<b>-20</b>	<b>25</b>	<b>70</b>
Operation humidity, <b>RH</b> (no condensation)		<b>10%</b>		<b>90%</b>











