

# BS-CH004 Safety Charging Car in Office Classroom Charge Smartphone Tablet

Input voltage	100-240V
Input Frequency	47-63HZ
Input power	600W (optional 200W/400W/800W)
The output voltage	5.0 0.2/_ 0.3V
Output current	0.5-2.1A
Output current limiting protection point	3A
Output short circuit protection	≥3A
Output overvoltage protection	≥5.5V DC ,If locked, power on again can be resuming
Output ripple and noise	≤100
Adjustable output voltage range	DC 4.75-5.5V
Dielectric strength	Input to output 2000Vac/10mA/1min (no arc, no breakdown)
Dielectric strength	Input to ground 2000Vac/10mA/1min (no arc, no breakdown)
Dielectric strength	Output to ground 1500Vac/10mA/1min (no arc, no breakdown)
GFCI	1PC□1.0mA(Vin=220Vac)
Cooling fan	5PC (optional 2pc/4pc/6pc)
Ground wire	2PC~4PC
Adapter cable	16~32~48~52~64PCS





When the device is charging the green light

Blue light flashes when data transfer

Door Handle & Lock



Ergonomic Handle

Air Vents





 PANTONE 426C

 PANTONE 8003C

 PANTONE 426C

 PANTONE 426C



 PANTONE 8003C

 PANTONE 3272C

 PANTONE 426C

 PANTONE 426C




 PANTONE 8003C

 PANTONE 1807C

 PANTONE 426C

 PANTONE 426C



 PANTONE COOL GRAY 8C

 PANTONE 7527C

 PANTONE COOL GRAY 5C

 PANTONE 7527C

**Share Our Others Good Products To You:**

**Fingerprint 4G LTE Smart Phone,360°Rotation Tablet  
PC,Super Slim Laptop**