

BS-CH004 100-240V 47-63HZ 600W (200W/400W/800W) 5.0 0.2/_ 0.3V 0.5-2.1A 3A 3A ≥5.5V DC ≤100 DC4.75-5.5V 2000Vac/10mA/1min (2000Vac/10mA/1min) 1500Vac/10mA/1 (1500Vac/10mA/1) 1PC 1.0mA (Vin=220Vac) 5PC (2PC/4PC/6PC) 2PC~4PC 16 32 48 52 64

電圧	100-240V
周波数	47-63HZ
容量	600W (200W/400W/800W)
電圧調整	5.0 0.2/_ 0.3V
電流調整	0.5-2.1A
最大電流	3A
最大電圧	3A
入力電圧	≥5.5V DC
入力電流	≤100
出力電圧	DC4.75-5.5V
電圧精度	2000Vac/10mA/1min (2000Vac/10mA/1min)
電流精度	2000Vac/10mA/1min (2000Vac/10mA/1min)
電圧精度	1500Vac/10mA/1 (1500Vac/10mA/1)
GFCI	1PC 1.0mA (Vin=220Vac)
電圧精度	5PC (2PC/4PC/6PC)
電流精度	2PC~4PC
電圧精度	16 32 48 52 64







When the device is charging the green light



Blue light flashes when data transfer



Door Handle & Lock



Ergonomic Handle



Air Vents



 PANTONE 426C

 PANTONE 8003C

 PANTONE 426C

 PANTONE 426C



 PANTONE 8003C

 PANTONE 3272C

 PANTONE 426C

 PANTONE 426C



 PANTONE 8003C

 PANTONE 1807C

 PANTONE 426C

 PANTONE 426C

