

400W ecoflow

PPS K400W / 404WH

PPS K400W for camping
hiking travel or anywhere you need power



Enjoy adventure time outdoors

PPSK400W is the best partner for your travel. 9 small devices can be charged meanwhile which offer you more time feeling the alive world. Any plans for hiking, camping or photo taking? Here we are ready.



Free Switch



Charge Anytime



Safe and Reliable



Multi-protection



Various Outputs



Smart Control



LED Display



Pure Sine Wave

Quality guarantee

■ 1st-class lithium battery

UL PSE FCC CE RoHS certification, short-circuit protection, fire prevention and high technology charging management system

■ Smart inverter

Adopts new inverting system to strengthen the protections for over current, short circuit, over charge, over load and over voltage. No damage for any machine, more safer.



Wall-mounted, Car and Solar panel
charging supported
(100W/18V solar panel suggested)



Put solar panel in the sunniest place





Product parameter

General parameters	Built-in battery	High quality lithium ion battery
	battery capacity	404Wh (11.1V, 36.4AH)
	input recharging	DC15V/4.0A (5521 DC port)
	solar panel charging	DC5521 13V~22V/4.0A
	Fully Charged Time	DC 15V: 7~8 Hours
	DC output	USB Port: 1 * USB 5V~9V/2A, QC 3.0; 2 * USB 5V/3.1A; Typ-c Port: 1 * Type-c 5V~9V/2A, QC3.0; 5521 DC output: 3 * DC 9~12.6V/10A (12A Max total); 1 * Cigarette Lighter adapter
	AC output	1 x AC pure sine wave output
	AC continuous output power	400W
	Max. AC output power	800W
	lighting	5W LED light (on the backside)
	Operating temperature	-10°C-40°C
	lifecycle	> 600 times
	Product protection	a.Short circuit protection b.Overcurrent protection c.Overvoltage protection d.Undervoltage protection e.Overload protection f.Over temperature protection
	Package included	1 x portable solar generator 1 x power adapter 1 x AC line 1 x user manual 1x Car charger
Adapter parameters	Machine certification	PSE FCC CE ROHS MSDS UN38.3 Air transport report,Marine transportation report
	Machine insurance	China Ping An \$4.41 million product global safety insurance
	Output	15V 4A
Input charging function	DC interface	5521
	shape	Desktop
	Support power adapter charging	Support
battery	Support solar panel charging	Support
	Support car charging	Support
battery	battery brand	Chuang Ming Brand
	Battery model specifications	18650
	Single cell capacity	2600 MAH
	Battery series parallel	3 series 14 parallel
	Cell voltage	3.7V
	Battery voltage	11.1V
	Battery power retention (1 year later)	about 80%
	Battery charge and discharge life	> 1000 times, Capacity is maintained at approximately 80%
structure	Dust/waterproof rating	No
	Product dimension CM	235*155*155 MM
	net weight	about 4.0KG
	Material	ABS plastic , plastic shell fire rating 94-V0;
	Product color matching	Can be freely matched by customers (quantity required: 500 pcs)
Product packaging	Product packaging	Carrying case neutral
	Carrying case dimension	L325XW209XH208mm
	Single carrying case weight	5.0KG
	Carton size	440 x340 x235mm
	Number of outer boxes	2 PCS/CTN
	Package weight	Gross weight: 10.5 kg
Use scene mode	Applicable to power outages, outdoor operations, night market electricity, emergency rescue, medical, household energy storage, etc.	
Delievry time	Normal 30 days, detailed discussion according to the actual situation.	

