

# 矿机矿机 S17 Pro 53T 矿机 矿机 矿机矿机

Hashrate & Power				
Hashrate, TH/s	Low Power		36~48.00	+3% (1-1)
	Normal		53	55.95
	Turbo		53~62.00	+3% (1-2)
Power efficiency on wall @25°C, J/TH	Low Power	36.00		39.60
	Normal	39.50		43.45
	Turbo	45.00		49.50
Power efficiency on wall @40°C, J/TH	Low Power	38.22		42.05
	Normal	41.73		45.90
	Turbo	47.99		52.79
Power on wall, Watt (1-3)	Low Power	1296~1728		2079
	Normal	2094		2568
	Turbo	2385~2790		3371
Power supply AC input voltage, Volt (1-4)		200	220	240
Power supply AC input current, Amp(1-5)	Low Power		5.89~7.85	10.40
	Normal		9.52	12.84
	Turbo		10.84~12.68	16.86
Power supply Input AC Frequency Range, Hz		47	50	63
Hardware Configuration				
Quantity of hash chips		144		
Quantity of hash boards		3		
Networking connection mode		RJ45 Ethernet 10/100M		
Miner Size (Length*Width*Height, w/o package),mm(2-1)		298.2*178.0*296.6		
Net weight, kg (2-2)		9.5		
Noise, dBA @25°C (2-3)				82
Environment Requirements				
Operation temperature, °C		0	25	40
Storage temperature, °C		-20	25	70
Operation humidity, RH(no condensation)		10%		90%











