□□□□□□□□ T15 □□ 23TH/s □□□□ Asice □□□□□

Detailed Characteristics		Value		
		Min	Typ	Max
Hashrate & Power				
Hashrate, **TH/s**	**Normal**		23.00	23.45
	Low Power		17.50~21	+3% (1-1)
Power efficiency on wall @**25°C**, **J/TH**	**Normal**	67.00		71.69
	Low Power	60.00		64.20
Power efficiency on wall @**40°C**, **J/TH**	**Normal**	70.52		75.46
	Low Power	62.92		67.32
Power on wall, **Watt** (1-2)	**Normal**	1541		1770
	Low Power	1050		1456
Power supply AC input voltage, **Volt** (1-3) 200		200	220	240
Power supply AC input current, **Amp**(1-4)	**Normal**		7.00	8.85
	Low Power		4.77	7.28
Power supply Input AC Frequency Range, **Hz**		47	50	63
Hardware Configuration				
Quantity of hash chips			180	
Quantity of hash boards			3	
Networking connection mode			RJ45 Ethernet 10/100M	
Miner Size (Length*Width*Height, w/o package),**mm**(2-1)			205*175*279	
Net weight, **kg** (2-2)			6.6	
Noise, **dBA** @25°**C** (2-3)				76