

Enjoy adventure time outdoors

PPS K400W is the best partner for your travel. 9 small devices can be charged meanwhile which offer you more time feeling the alive world. Any plans for hiking, camping or photo taking? Here we are ready.





Quality guarantee

1st-class lithium battery UL PSE FCC CE RoHS certification, short-circuit protection, fire prevention and high technology charging management system

Smart inverter

Adopts new inverting system to strengthen the protections for over current, short circuit, over charge, over load and over voltage.

No damage for any machine, more safer.



Put solar panel in the sunniest place





Product parameter

| General parameters | Built-in battery | High quality lithium ion battery | | | |
|-------------------------|--|--|--|--|--|
| | battery capacity | 404Wh (11.1V, 36.4AH) | | | |
| | input recharging | DC15V/4.0A (5521 DC port) | | | |
| | solar panel charging | DC5521 13V~22V/4.0A | | | |
| | Fully Charged Time DC output | DC 15V: 7~8 Hours USB Port: 1 * USB 5V~9V/2A, QC 3.0; 2 * USB 5V/3.1A; Typ-c Port: 1 * Type-c 5V~9V/2A, QC3.0; 5521 DC output: 3 * DC 9~12.6V/10A (12A Max total); 1 * Cigarette Lighter adapter | | | |
| | AC output | 1 x AC pure sine wave output | | | |
| | AC continuous output power | 400W | | | |
| | Max. AC output power | 800W | | | |
| | lighting | 5W LED light (on the backside) | | | |
| | Operating temperature | -10°C-40°C | | | |
| | lifecycle | > 600 times | | | |
| | Product protection | a.Short circuit protection b.Overcurrent protection c.Overvoltage protection d.Undervoltage protection e.Overload protection f.Over temperature protection | | | |
| | Package included | 1 x portable solar generator 1 x power adapter 1 x AC line 1 x user manual 1x Car charger | | | |
| | Machine certification | PSE FCC CE ROHS MSDS UN38.3 Air transport report, Marine transportation report | | | |
| | Machine insurance | China Ping An \$4.41 million product global safety insurance | | | |
| | Output | 15V 4A | | | |
| Adapter parameters | DC interface | 5521 | | | |
| | shape | Desktop | | | |
| Input charging function | Support power adapter charging | Support | | | |
| | Support solar panel charging | Support | | | |
| | Support car charging | Support | | | |
| | battery brand | Chuang Ming Brand | | | |
| | Battery model specifications | 18650 | | | |
| | Single cell capacity | 2600 MAH | | | |
| battery | Battery series parallel | 3 series 14 parallel | | | |
| | Cell voltage | 3.7V | | | |
| | Battery voltage | 11.1V | | | |
| | Battery power retention (1 year later) | about 80% | | | |
| | Battery charge and discharge life | >1000 times, Capacity is maintained at approximately 80% | | | |
| structure | Dust/waterproof rating | No | | | |
| | Product dimension CM | 235*155*155 MM | | | |
| | net weight | about 4.0KG | | | |
| | Material | ABS plastic , plastic shell fire rating 94-V0; | | | |
| | Product color matching | Can be freely matched by customers (quantity required: 500 pcs) | | | |
| Product packaging | Product packaging | Carrying case neutral | | | |
| | Carrying case dimension | L325XW209XH208mm | | | |
| | Single carrying case weight | 5.0KG | | | |
| | Carton size | 440 x340 x235mm | | | |
| | Number of outer boxes | 2 PCS/CTN | | | |
| | Package weight | Gross weight: 10.5 kg | | | |
| Use scene mode | Applicable to power outages, outdoor operations, night market electricity, emergency rescue, medical, household energy storage, etc. | | | | |
| | | | | | |
| Delievry time | Normal 30 days, detailed discussion according to the actual situation. | | | | |