BS-CH004 Safety Charging Car in Office Classroom Charge Smatphone Tablet

Input voltage	100-240V
Input Frequency	47-63HZ
Input power	600W (optional 200W/400W/800W)
The output voltage	5.0 0.2/_0.3V
Output current	0.5-2.1A
Output current limiting protection point	3A
Output short circuit protection	≥3A
Output overvoltage protection	≥5.5V DC ,If locked, power on again can be resuming
Output ripple and noise	≤100
Adjustable output voltage range	DC 4.75-5.5V
Dielectric strength	Input to output 2000Vac/10mA/1min (no arc, no breakdown)
Dielectric strength	Input to ground 2000Vac/10mA/1min (no arc, no breakdown)
Dielectric strength	Output to ground 1500Vac/10mA/1min (no arc, no breakdown)
GFCI	1PC□1.0mA(Vin=220Vac)
Cooling fan	5PC (optional 2pc/4pc/6pc)
Ground wire	2PC~4PC
Adapter cable	16~32~48~52~64PCS

When the device is charging the green light

Blue light flashes when data transfer

Door Handle & Lock

Ergonomic Handle

Air Vents

PANTONE 426C

PANTONE 8003C

PANTONE 426C

PANTONE 426C

PANTONE 8003C

PANTONE 3272C

PANTONE 426C

PANTONE 426C

PANTONE 8003C

PANTONE 1807C

PANTONE 426C

PANTONE 426C

PANTONE COOL GRAY 8C

PANTONE 7527C

PANTONE COOL GRAY 5C

PANTONE 7527C

Share Our Others Good Products To You:

Fingerprint 4G LTE Smart Phone,360°Rotation Tablet PC,Super Slim Laptop