

Original Antminer Power Supply PSU For S9/L3/D3 Antminer Miner

| | |
|---------------------------------------|---------------|
| DC Voltage | 12.15V |
| Rated Current (220V input) | 133A |
| Rated Current (110V input) | 100A |
| Rated Power (220V input) | 1600W |
| Rated Power (110V input) | 1200W |
| Ripple & Noise | <1% |
| Voltage Regulation | <2% |
| Source Regulation | <1% |

| | |
|---------------------------------------|---|
| Load Regulation | <1% |
| Setup, Rise Time | <2S |
| Power off Protection Trip Time | >9mS |
| Interface Type | 5 pairs of 6 pin PCI-E connectors (i.e. 10 connectors) |
| Noise Level | <43DB |
| Voltage Range | 100-240V AC |
| Starting Voltage | 95-105V AC |
| Frequency Range | 47-63Hz |
| Power Factor | >0.95 (full load) |
| Leakage Current | <1.5mA (220V 50Hz) |
| Low-voltage input | 80-89V AC |

| | |
|------------------------------|---|
| Output Short Circuit | Yes |
| Output Overcurrent | 134-185A max |
| Overheat Protection | Yes |
| Operating Temperature | -20°C - 50°C |
| Operating Humidity | 20% - 90% relative humidity (non-condensing) |
| Dimensions | 220mm*108mm*62mm |
| Fan | Forced-air cooling |



